



TECHNICAL DATA SHEET

OIL.CARE

Maintenance product for oil treated indoor and outdoor wood floors



1 Lt

DESCRIPTION

OIL.CARE is an emulsion of waxes, natural oils, modified oils and special anti UV additives for the maintenance of outdoor and/or indoor floors treated with oils from the W.OIL range. Cobalt and Methyl Ethyl Ketoxime-free. The oily component of OIL.CARE repairs the treatment oil that has deteriorated due to exposure to atmospheric agents and it penetrates into the wood providing in-depth protection, the water-repellent wax prevents water from entering the pores in the wood, while the anti-UV additives delay the deterioration of the lignin. OIL.CARE is also suitable for protecting all wood products treated with impregnation products, both indoors and out (garden furniture, wooden partitions, beams, fences, WPC...).

TECHNICAL DATA CHEMICAL-PHYSICAL CHARACTERISTICS at 20°C (indicative values not constituting product specifications):

Application method	Cotton cloth
Dilution in water	20/25%
Recommended frequency of use	once every 1-2 months
Ready for traffic (minutes)	30
Ready for traffic and for maximum performance (hours)	12
Stability and storage (in original, unopened containers stored in a cool, dry place)	12 months
Standard packaging (Lt)	1

APPLICATION

Always shake the product before use. Dilute the product with 4-5 parts of clean water. Distribute a thin, even layer over the floor using a cotton cloth. Alternatively, the product can be sprayed and then rubbed in evenly with a cotton cloth or with a polisher using a beige or white pad. Do not use excessive quantities of product to avoid creating shiny patches and/or stickiness. The frequency of the maintenance can be set according to requirements. In general, OIL.CARE is applied once every 1-2 months, but according to the traffic and the atmospheric conditions, it may be necessary to apply the product more often. For normal cleaning operations, we recommend washing the floor with water and a neutral detergent. The treated surfaces are ready for traffic after 30 minutes, but it is highly recommended to carry out the treatment when the floor can be left without traffic for the following 12 hours.

NOTES

Shake well before use.
Store above freezing.

Safety precautions. Keep the product in a tightly closed, upright container in a cool place away from sources of heat. The product is classified and coded in compliance with EC Directives/regulations concerning hazardous substances. The information for the user is given in the relevant safety sheet. Empty containers or those containing slight traces of the product must be disposed of in accordance with local regulations. VerMeister S.p.A. guarantees that the details given in this sheet are provided to the best of the company's technical-scientific knowledge and experience; however, the company cannot be held responsible in any way for the results obtained with the products as the conditions of application are beyond the company's control. It is always advisable to check the suitability of the product to each specific circumstance. This sheet cancels and replaces all previous editions.